



ANOS






















Available Options

Enhance, Extend and Enjoy
Accessories extend your notebook's power and utility. Take the lightweight and well-designed accessories with you to increase productivity wherever you are, or leave them at home or in the office so you can travel light.

MODELS	Included †† Must be used with AC adapter * Compatible only with Windows® XP notebooks ** Compatible only with Windows® 2000 notebooks	OPTICAL DRIVES				BATTERIES/CHARGER												
		16X MAX. CD-ROM DRIVE	8X/24X MAX. EXTERNAL CD-RW DRIVE	8X MAX. DVD-ROM DRIVE	8X8X4X/24X CD-RW/DVD COMBO DRIVE	STANDARD CAPACITY	DOUBLE- CAPACITY	QUAD- CAPACITY	STANDARD CAPACITY	STANDARD CAPACITY	STANDARD CAPACITY	DOUBLE CAPACITY	STANDARD CAPACITY	DOUBLE CAPACITY	BATTERY CHARGER	STANDARD CAPACITY	DOUBLE- CAPACITY	QUAD- CAPACITY
		PCGA- CDS1A	PCGA- CDRW52	PCGA- DVS1/A	PCGA- CRWD1	PCGA- BP51A	PCGA- BP52A	PCGA-BP54	PCGA- BP71A	PCGA-BP2E	PCGA-BP2R	PCGA-BP4R	PCGA-BP2S	PCGA-BP4S	PCGA-BP5	PCGA- BP51A/L	PCGA- BP52A/L	PCGA- BP54/L
		GR290/K/P								•								
		GR270/K/P								•								
GR250/K/P								•										
SR33/K	†	•	•									•	•					
SR27K	†	•	•									•	•					
R505JS/K/P	•	**		†† *						•	•							
R505JE/K/P	•	**		†† *						•	•							
R505JL/K/P	•	**		†† *						•	•							
C1MV	†			•										•	•	•	•	
C1VP/K	•	††	††		•	•	•							•	•	•	•	
FX390/K/P								•										
FX370/K/P								•										
FX340/K/P								•										
FX310/K/P								•										
FXA36								•										
FXA33								•										
FXA32								•										

Optical Drive Speeds (max): PCGA-CRW1D: 4XW, 8XRW, 24XR, 8XDVD PCGA-CD51A: 16XCDR PCGA-CDRW52: 4XW, 8XRW, 24XR PCGA-DVD51/A: 8XDVD, 24XCDR PCGA-DSM5: 8XW, 4XRW, 24XR, 8XDVD
PCGA-DSD5: 24XCDR 8XDVD

Available Options

MODELS	↑ Included ↑ Must be used with AC adapter * Compatible only with Windows® XP notebooks ** Compatible only with Windows® 2000 notebooks	AC ADAPTERS					DOCKING STATIONS/ PORT REPLICATORS				CARRYING CASES				MEMORY				WIRELESS LAN		OTHER	
																						
	AC ADAPTER PCGA-AC19V1	AC ADAPTER PCGA-AC16V1	AC ADAPTER PCGA-AC16V2	AC ADAPTER PCGA-AC16V	AC ADAPTER PCGA-AC16V4	SLIMDOCK™ DOCKING STATION PCGA-DSM5	SLIMDOCK™ DOCKING STATION PCGA-DSD5	PORT REPLICATOR PCGA-PRFX1	PORT REPLICATOR PCGA-PRGR1	CARRYING CASE PCGA-CCB	CARRYING CASE PCGA-CCR5	CARRYING CASE PCGA-CCF	NOTEBOOK BACKPACK PCGA-CCP1	6MB MEMORY PCGA-MM164	64MB MEMORY PCGA-MM64S	128MB MEMORY PCGA-MM128S	128MB MEMORY PCGA-MM128T	WIRELESS LAN PRO ACCESS POINT PC CARD PCWA-A200	WIRELESS LAN PC CARD PCWA-C100	USB FLOPPY DRIVE PCGA-UFD5	USB MOUSE PCGA-UMS1/A	
	GR290/K/P			•					•				•	•				•	•	•	•	
	GR270/K/P				•					•			•	•				•	•	•	•	
	GR250/K/P				•					•			•	•				•	•	•	•	
	SR33/K		•								•	•	•	•		•	•		•	•	•	•
	SR27K		•								•	•	•	•		•	•		•	•	•	•
	R505JS/K/P	•					†	•			•	•	•	•					•	•	•	•
	R505JE/K/P	•					•	•			•	•	•	•					•	•	•	•
R505JL/K/P	•					•	†			•	•	•	•					•	•	•	•	
C1MV					•					•	•	•	•				•	•	•	•	•	
C1VP/K			•							•	•	•	•	•			•	•	•	•	•	
FX390/K/P	•							•				•	•					•	•		•	
FX370/K/P	•							•				•	•					•	•		•	
FX340/K/P	•							•				•	•					•	•		•	
FX310/K/P	•							•				•	•					•	•		•	
FXA36	•							•				•	•					•	•		•	
FXA33	•							•				•	•					•	•		•	
FXA32	•							•				•	•					•	•		•	

Carrying Case Exterior Dimensions: PCGA-CCF: 12.5" x 15" x 6.5" PCGA-CCR5: 12" x 16" x 5" PCGA-CCB: 10.8" x 14" x 3.5" PCGA-CCP1: 15.75" x 12.5" x 8.25"

Specifications Continued

SPECIFICATIONS		GR-SERIES			SR-SERIES		R505-SERIES		
		GR290/K/P	GR270/K/P	GR250/K/P	SR33/K	SR27K	R505JS/K/P	R505JE/K/P	R505JL/K/P
	MEMORY CONFIGURATION	S1: 256MB + S2: open	S1: 256MB + S2: open	S1: 256MB + S2: open	S1: 64MB + S2: 64MB	S1: 128MB + S2: open	S1: 128MB + S2: 128MB	S1: 128MB + S2: open	S1: 128MB + S2: open
	MEMORY TYPE	PC-133	PC-133	PC-133	PC-100 MicroDIMM	PC-100 MicroDIMM	PC-100	PC-100	PC-100
	PC CARD SLOTS	Two Type II/One Type III	Two Type II/One Type III	Two Type II/One Type III	One Type II	One Type II	One Type II	One Type II	One Type II
	V.90 MODEM (INTEGRATED)	Yes	Yes		Yes	Yes	Yes	Yes	Yes
	ETHERNET	10Base-T/100Base-TX	10Base-T/100Base-TX	10Base-T/100Base-TX	N/A	N/A	10Base-T/100Base-TX	10Base-T/100Base-TX	10Base-T/100Base-TX
	I.LINK* (IEEE1394)*	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	3D GRAPHICS ENABLED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	DATA TRANSFER MODE	ATA-66	ATA-66	ATA-66	ATA-66	ATA-66	ATA-66	ATA-66	ATA-66
PARALLEL PORT	Yes	Yes	Yes	No	No	Yes (on supplied Docking Station)	On Optional Docking Station	Yes (on supplied Docking Station)	
SERIAL PORT	On Optional Port Replicator	On Optional Port Replicator	On Optional Port Replicator	No	No	Yes (on supplied Docking Station)	On Optional Docking Station	Yes (on supplied Docking Station)	
USB PORT	3	3	3	1	1	2 on Unit/ 3 when Docked	2	2 on Unit/ 3 when Docked	
VGA PORT	Yes	Yes	Yes	Yes w/Supplied Adaptor	Yes w/Supplied Adaptor	Yes	Yes	Yes	
MOUSE OR KB PORT	On Optional Port Replicator	On Optional Port Replicator	On Optional Port Replicator	No	No	No	No	No	
HEADPHONE JACK	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
AUDIO IN	Mic and Line	Mic and Line	Mic and Line	Yes	Yes	Mic Only	Mic Only	Mic Only	
VIDEO OUT	NTSC	NTSC	NTSC	No	No	No	No	No	
BATTERY - STD/OPT	PCGA-BP2E/PCGA-BP2E	PCGA-BP2E/PCGA-BP2E	PCGA-BP2E/PCGA-BP2E	PCGA-BP2S/BP4S	PCGA-BP2S/BP4S	PCGA-BP2R/BP4R	PCGA-BP2R/BP4R	PCGA-BP2R/BP4R	
STD BATTERY LIFE - 1/2	2-3/4-6 hours	2.5-3.5/5-7 hours	2.5-3.5/5-7 hours	3.5-5.0/7-10 hours	3.5-5.5/7-11 hours	3-4.5/6.5-8.5 hours	3-4.5/6.5-8.5 hours	3-4.5/6.5-8.5 hours	
AC ADAPTER	PCGA-AC16V	PCGA-AC16V	PCGA-AC16V	PCGA-AC16V1	PCGA-AC16V1	PCGA-AC19V1	PCGA-AC19V1	PCGA-AC19V1	

Specifications Continued

[illegible]