

Thiele/Small parameters Système de haut-parleurs

	XS-L1055G	XS-L1065G		XS-L1255G	XS-L1265G	
Impedance Impédance	4Ω	2Ω	8Ω	4Ω	2Ω	8Ω
d (mm)	210	210		260	260	
d (inch)	8.3	8.3		10.3	10.3	
Rdc (Ω)	3.5	1.8	7.3	3.6	1.9	7.4
Fs (Hz)	47.9	41.2	41.2	32.4	31.5	31.5
Qts	0.5	0.37	0.38	0.41	0.36	0.34
Qes	0.63	0.42	0.43	0.52	0.41	0.39
Qms	2.56	3.47	3.47	1.89	2.86	2.7
Vas (Lit.)	10.3	15.4	17.9	44.9	30.9	37.9
Vas (Cu.ft)	0.36	0.54	0.63	1.58	1.09	1.34
Mms (g)	180	139.5	162.5	212.3	325.4	266.2
Lvc (mH)	0.6	0.7	2.9	0.6	0.7	2.8
Xmax (mm)	10.5	10.5		10.5	10.5	
Xmax (inch)	0.41	0.41		0.41	0.41	
BL (Tm)	17.4	12.5	26.7	17.3	17	31.6
Enclosure vol. (Net) Vol. du boîtier (net)	17 Lit. (0.6 cu.ft)	17 Lit. (0.6 cu.ft)		28 Lit. (1 cu.ft)	28 Lit. (1 cu.ft)	

Recommended Enclosure: Sealed type

Boîtier recommandé: de type scellé