

Features & Specs

Amplifiers

FEATURES:	XM-2150GSX	XM-475GSX	XM-5150GSX	XM-1600GSD
Dual Mode Capable	•	•	•	–
Test Tone	•	•	•	•
Speaker Level Inputs	•	•	–	•
Hi Pass (12dB/oct) (Hz)	50-300	50-300	50-300	–
Low Pass (12dB/oct) (Hz)	50-300	50-300	50-300	50-300
Status Indicator	•	•	•	•
EQ (40 Hz) (dB)	0-10	0-10	0	0-10
Line-Out (Pair)	1	0	0	1
Line-In (Pair)	1	2	3	1
Protection Circuitry	•	•	•	•
Channels	2/1	4/3/2	5/3	1
Output Type	MOSFET	MOSFET	MOSFET	MOSFET
Power Supply	MOSFET	MOSFET	MOSFET	MOSFET
SPECIFICATIONS:				
Ad Hoc Power (4 Ω) @14.4VDC THD (%)	150 x 2 0.04	75 x 4 0.04	40 x 4 + 150 0.04	300 x 1 0.02
Bridged 4 Ω THD (%)	380 x 1 0.1	200 x 2 0.1	120 x 2 0.1	–
Bridged 2 Ω THD (%)	190 x 2 0.1	100 x 4 0.1	60 x 4 + 180 0.1	600 x 1 0.6
Bridged 1 Ω THD (%)	NA	NA	NA	1000 x 1 1.2
Max Power (watts)	760	800	880	1200
Freq Response (+/-3dB) (Hz)	5-50k	5-50k	5-50k	5-300k
S/N Ratio (dB)	>100	>100	>100	>100
Channel Sep (dB)	>80	>80	>80	>80
Dimensions: W (inch)	14-1/8	14-1/8	14-1/8	14-1/8
H (inch)	2	2	2	2
D (inch)	10-1/2	10-1/2	10-1/2	10-1/2