

Features & Specs

Speakers & Subwoofers

Model	Max Power (watts)	RMS Power (watts)	Freq Response	Sensitivity 1W/1M	Nominal mp (Ws)	Driver Config (inch)	Cone Material	Magnet Material	Mounting Dia. (inch)	Mounting Depth (inch)	Mass (lb/oz)
COMPONENT SERIES:											
XS-HF500G	170	55	32-30kHz	90dB	4	6/1	Aluminum	Samarium/Neodymium	4-3/4/ 1-5/8	2-1/8	1/12
XS-HF600G	200	60	30-30kHz	90dB	4	6-3/8/1	Aluminum	Samarium/Neodymium	5/ 1-5/8	2-1/8	1/15
XS-L836	500	170	30-3k	87dB	4	8	Polypropylene	Ferrite	7-1/4	4	6/3
XS-L1036	700	250	25-2.8k	88dB	4	10	Polypropylene	Ferrite	9-1/4	5	7/15
XS-L1236	900	300	20-2.5k	89dB	4	12	Polypropylene	Ferrite	11	5-3/8	11/11
XS-L1536	1000	350	18-1.5k	89dB	4	15	Polypropylene	Ferrite	13-7/8	7	16/12
XS-L1046	900	350	25-2.8k	88dB	4	10	Aluminum	Ferrite	9-1/4	5	7/15
XS-L1246	1200	400	20-2.5k	89dB	4	12	Aluminum	Ferrite	11	5-3/8	11/11
XS-HD690G	230	60	28-28k	90	4	6-3/8 x 9-1/2	Aluminum	Ferrite	6 x 8-3/4	3-1/2	4/4
XS-HD160G	200	50	30-28k	90	4	6-3/8	Aluminum	Ferrite	5	2-1/2	2/10
V-SERIES:											
XS-V1332	150	40	45-25k	89	4	5-1/4/1-7/16/7/16	HOP	F/N	4-5/8	2	1/8
XS-V1632	200	50	30-25k	90	4	6-1/4 x 9/1-7/16/7/16	HOP	F/N	5	1-13/16	1/9
XS-V6932	220	50	30-26k	91	4	6 x 9/2-5/8/1	HOP	F/F	5-3/4 x 8-1/2	3	2/7
XS-V6942	260	60	28-28k	91	4	6 x 9/2-5/8/1/1	HOP	F/F	5-3/4 x 8-1/2	3-1/4	2/15
W-SERIES:											
XS-W1320	120	35	40-25kHz	90dB	4	5-1/8	HOP/Paper	F/N	4-5/8	1-13/16	1/9
XS-W1620	160	50	30-25kHz	91dB	4	6-3/8	HOP/Paper	F/N	5	1-13/16	1/10
XS-W6920	200	50	28-26kHz	92dB	4	6-3/8 x 9-1/2	HOP/Paper	F/N	5-3/4 x 8-1/2	2-7/8	2/9
MARINE SERIES & SPECIAL APPLICATION SPEAKERS:											
XS-MP61	80	20	40-20kHz	90dB	4	6-1/2 Dual Cone	Polypropylene	Strontium	5	2-1/4	1/10
XS-MP62	140	35	40-20kHz	90dB	4	6-1/2/2-1/8	Polypropylene	Strontium	5	2-7/8	1/10
XS-33	40	10	90-20kHz	89dB	4	3	Paper	Strontium	3-1/2	1-1/2	1/0
XS-4624	80	20	45-25kHz	88dB	4	4 x 6/1	Polyprop/Poly Film	Strontium	4 x 6-1/8	1-7/8	1/3
XS-5726	120	40	40-25kHz	89dB	4	5 x 7/1	Polyprop/Poly Film	Strontium	5 x 7-1/4	2-1/4	1/9
XS-F1721	140	35	35-30kHz	90dB	4	6-1/2/1-3/16	Polypropylene/PEI	Strontium	5-1/2	1-13/16	1/7
Model	XS-L836	XS-L1036	XS-L1236	XS-L1536		XS-L1046	XS-L1246				
Impedance (ohms)	4	4	4	4		4	4				
d (mm)	165	210	260	340		210	260				
d (inch)	6.5	8.3	10.3	13.4		8.3	10.3				
Rdc (ohms)	3.6	2.8	3.3	3.2		2.8	3.2				
Fs (Hz)	33.85	25.4	25.6	23.0		26.8	26.1				
THEILE/SMALL PARAMETERS:											
Qts	0.45	0.33	0.36	0.42		0.36	0.37				
Qes	0.48	0.35	0.39	0.46		0.39	0.40				
Qms	7.26	4.69	5.18	5.66		4.96	5.11				
Vas (lit.)	14.9	51.6	66.1	204.1		47.7	56.3				
Vas (Cu ft.)	0.53	1.82	2.33	7.20		1.68	1.99				
Mms (g)	95.6	130.7	226.0	248.5		129.2	253.4				
Lvc (mH)	1.3	1.2	1.2	1.3		1.2	1.3				
Xmax (inch)	0.21	0.17	0.2	0.16		0.17	0.2				
Bl (Tm)	12.4	13.0	17.5	16.1		12.6	18.4				
Enclosure Vol (net) (Lit./Cu. ft.)	15/0.5	20/0.7	28/1.0	40/1.4		20/0.7	28/1.0				