

Tech Fax # 10628

April 21, 1999

How To Connect A Sony Notebook Or Docking Station To A Computer Monitor. PCG 505G/GX 505F/FX 505TS/TX 705 707 717 719 729 731 735 748 808 812 818 838 PCGA DH7 DB7 DH8 DB8

Please scroll to the appropriate model section below and follow the instructions.

NOTE: This information is also available in the Users guide which shipped with the system.

I. PCG 505G/GX 505F/FX 505TS/TX

1. With the computer off, connect the port replicator to the I/O port on the left side of the unit.
2. Connect the external display cable to the monitor port on the port replicator.
3. Connect the power cord to the external display and power outlet.
4. Turn on the external display and the computer.
5. To select display output, press the FN and F7 keys simultaneously to toggle between LCD Only, Display Only, or Both.

II. PCG 705 707 717 719 729 731 735 748 808 812 818 838

1. Open the right protective door on the back of the notebook.
2. Plug the display cable into the monitor connector (indicated by the blue symbol on the door).
3. Plug one end of the display power cord into the display, and the other end into an AC outlet.

NOTE: If this is a not a multimedia computer display, skip to step 6.

4. Plug the speaker cable into the speaker connector on the side of the notebook which is indicated by the headphone symbol (the leftmost jack).
5. Plug the microphone cable into the microphone connector on the back of the notebook which is indicated by the microphone symbol (the middle jack).
6. To select display output, press the FN and F7 keys simultaneously to toggle between LCD Only, Display Only, or Both.

III. PCGA DH7 DB7 DH8 DB8 Docking Stations

NOTE: The PCGA DH8 and DB8 Docking Stations are only compatible with the PCG 735 808 812 818 838 notebooks.

1. Plug the display cable into the monitor connector (indicated by the blue symbol on the top ports).
2. Plug one end of the display power cord into the display, and the other end into an AC outlet.

If this is not a multimedia computer display, skip to step 5:

3. Plug the speaker cable into the speaker connector on the back of the docking station which is indicated by the grey Line OUT jack.
4. Plug the microphone cable into the microphone connector on the back of the docking station which is indicated by the red microphone jack.
5. To select display output, press the FN and F7 keys simultaneously to toggle between LCD Only, Display Only, or Both.