

Receivers Step-Up Chart

STR-DE185	STR-DE595	STR-DE695
100W X 2 8Ω 40-20kHz, THD 0.09%	100W X 5 8Ω 1 kHz, THD 0.7%	100W X 6 8Ω 1kHz, THD 0.7%
Stereo	Dolby Digital™, dts®, Pro-Logic® II	Dolby Digital™-EX, dts®-ES, Pro-Logic® II, dts-neo6
A+B/A or B	A+B/A or B	A+B/A or B
Push Terminals	Push Terminals	Screw/Push Terminals Except B
Uni-Remote	Uni-Remote	PP Remote
	2 Opt/1 Coax	3 Opt/1 Coax
	HD 80Mhz Component	HD 80Mhz Component

STR-DE895	STR-DE995
100W X 6 (8Ω 20-20kHz, THD 0.09%) 110W X 6 (8Ω 1kHz, THD 0.7%)	100W X 7 (8Ω 20-20kHz, THD 0.09%) 110W X 7 (8Ω 1kHz, THD 0.7%)
Dolby Digital™-EX, dts®-ES, Pro-Logic® II, dts-neo6	Dolby Digital™-EX, dts®-ES, Pro-Logic® II, dts-neo6
A+B/A or B	A+B/A or B
Screw Terminals Except B	Screw Terminals
Learn/Macro/PP Remote	LCD Learn/Macro/PP Remote
4 Opt/1 Coax In Assignable	4 Opt/1 Coax In Assignable
HD 80Mhz Component	HD 80Mhz Component
	2nd Room Audio Out
	OSD, S-Video Upconversion

Items that appear in **bold** indicate this is a step up feature

= Video
 = Audio
 = Performance
 = Convenience