

TC-K630ES

DIMENSIONS

(WHD): 16 7/8"x4 5/8"x12 7/8"

WEIGHT: 11 lbs. 7 oz.

REQUIREMENTS: 120V AC
POWER: 60Hz

POWER

CONSUMPTION: 20 Watts

Scale 4:1

Front view of the unit showing dimensions:

- Overall width: 16 7/8"
- Overall height: 4 5/8"
- Height of the main display area: 4 1/4"
- Height of the bottom control area: 3/8"
- Bottom mounting flange width: 5/16"
- Distance from left flange to first vertical divider: 2 1/4"
- Distance between the two main vertical dividers: 11 3/4"
- Distance from the second vertical divider to the right flange: 2 1/4"

The front panel features a "Remote Sensor" on the left, a central display area with two circular indicators, and a right-side control area with several buttons and a large circular knob.

Technical drawing of a cassette door. The drawing shows a rectangular door with a textured surface. Two circular handles are positioned horizontally. Dimensions are provided for the overall size and internal components. A label indicates the door is open.

Dimensions:

- Overall width: $13 \frac{5}{8}"$
- Overall height: $1 \frac{5}{8}"$
- Distance from left edge to first handle: $2 \frac{1}{4}"$
- Distance between handles: $7"$
- Distance from second handle to right edge: $2 \frac{1}{4}"$
- Distance from left edge to bottom rail: $\frac{7}{8}"$
- Distance from right edge to bottom rail: $\frac{1}{2}"$

Label: **Cassette Door Open**

Diagram illustrating the rear panel connections:

- 1. Line In
- 2. Line Out
- 3. AC Cord

Contractor's Notes: