

**SONY.****XS-L1235/L1035/L835/MB835/L1235D4/L1035D4/L1035D6****Thiele/Small parameters  
Système de haut-parleurs**

	XS-L1235	XS-L1035	XS-L835	XS-MB835	XS-L1235D4		XS-L1035D4		XS-L1035D6	
Impedance Impédance	4Ω	4Ω	4Ω	4Ω	2Ω	8Ω	2Ω	8Ω	3Ω	12Ω
d (mm)	260	210	165	165	260		210		210	
d (inch)	10.3	8.3	6.5	6.5	10.3		8.3		8.3	
Rdc (Ω)	3.2	3.6	3.1	3	1.8	7.2	1.9	7.7	2.7	11.1
Fs (Hz)	23.5	26.6	31.8	28.9	24.9	23.8	28.9	27.3	28.2	27.6
Qts	0.39	0.43	0.45	0.33	0.48	0.45	0.43	0.43	0.43	0.43
Qes	0.43	0.48	0.49	0.34	0.52	0.49	0.48	0.47	0.47	0.48
Qms	4.9	3.96	4.87	8.28	5.84	5	4.49	4.36	4.54	3.7
Vas (Lit.)	104	49.6	17.26	25.4	61.1	91.5	31.1	44.7	30.3	44
Vas (Cu.ft)	3.67	1.75	0.61	0.9	2.16	3.23	1.1	1.58	1.07	1.55
Mms (g)	175.3	131.6	104.8	86.7	268.4	201.9	166.4	137.8	177.8	137.9
Lvc (mH)	1.2	1	1	1.3	0.7	2.8	0.7	2.7	1	3.7
Xmax (mm)	5	4.3	5.3	4.3	6.8		5.3		5.3	
Xmax (inch)	0.2	0.17	0.21	0.17	0.27		0.21		0.21	
BL (Tm)	13.8	12.8	11.5	11.7	11.9	21.1	10.8	19.7	13.4	23.5
Enclosure vol. (Net) Vol. du boîtier (net)	28 Lit. (1.0 cu.ft)	20 Lit. (0.7 cu.ft)	15 Lit. (0.5 cu.ft)	–	28 Lit. (1.0 cu.ft)		20 Lit. (0.7 cu.ft)		20 Lit. (0.7 cu.ft)	

Recommended Enclosure: Sealed type

Boîtier recommandé: de type scellé